

....

....

\$	CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC	RRRRRRRR RR		BBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBB
		\$		

SCF VO4

SCF VO4

15-Sep-1984 23:25:09 15-Sep-1984 22:53:28

Terminal Control Block Definitions for RTL SCR\$ facility File: SCRTCB.REQ Edit: RKR1001

Version:

'V04-000'

COPYRIGHT (c) 1978, 1980, 1982, 1984 BY DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS. ALL RIGHTS RESERVED.

THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY TRANSFERRED.

THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT CORPORATION.

DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.

FACILITY:

Screen Management

ABSTRACT:

This file contains the offsets for each variable in the Terminal Control Block. A TCB is allocated by the screen package for each channel/terminal.

AUTHOR: R. Reichert, CREATION DATE: 25-AUG-1982

MODIFIED BY:

1-001 - Original. RKR 25-AUG-1982

Terminal control block

MACRO

 $SCRSL_FLINK = 0, 0, 32, 0%,$

SCR\$L_BUFFER = 4. 0. 32. 0%.

SCR\$W_CHAN = 8, 0, 16, 0%,

SCR\$B_TYPE = 10, 0, 8, 0%,

Link pointer to next terminal control block Address of buffer for buffer mode

Channel number for this terminal

Terminal type

```
VAX-11 Bliss-32 V4.0-742
$255$DUA28:[VMSLIB.SRC]SCRTCB.REQ;1
                                                                                SCR$B_DEVTYP = SCR$W_DEVWIDTH = SCR$W_DEVPAGSIZ = SCR$L_DEVCHAR = SCR$L_AREA = SCR$L_ATTRMAP = SCR$L_MODFMAP = SCR$L_INE = SCR$L_COLUMN = SCR$L_ATTRMASK = SCR$L_STREAM = SCR$L_STREAM = SCR$W_IFI = S
                                                                                                                                                                                                             8. 0%.
16. 0%.
16. 0%.
32. 0%.
32. 0%.
32. 0%.
32. 0%.
32. 0%.
32. 0%.
32. 0%.
32. 0%.
32. 0%.
32. 0%.
32. 0%.
32. 0%.
32. 0%.
0058
0059
0061
00663
00665
00667
00668
00670
0077
0077
0077
00778
0081
0083
0088
0088
0088
0088
                                                                                                                                                                                                                                                                                Device type ($DCDEF)
Line width in characters
                             Lines on screen
                                                                                                                                                                                                                                                                                  Supported device characteristics
                                                                                                                                                                                                                                                                                  Size of screen maps
                                                                                                                                                                                                                                                                                Address of character array
Address of attribute array
Address of modified bit map
Current line
                                                                                                                                                                                                                                                                               Current column
OR'd attributes for ATTRMAP
User-assigned stream number
Context for RMS file calls
Context for RMS record calls
                                                                                                                                                                                                                                                                                  Quadword describing next two
                                                                                                                                                                                                                                                                                   locations
                                                                                                                                                                 = 56, 0, 32, 0%,
                                                                                  SCR$L_RTNADDR
                                                                                                                                                                                                                                                                                  Routine call-back address for
                                                                                                                                                                                                                                                                                 output
                                                                                                                                                                = 60. 0.
= 64. 0.
= 64. 0.
                                                                                 SCR$L_RTNARG
SCR$L_CONTROL
SCR$V_SCROLL
                                                                                                                                                                                                                                                                                 Argument to pass to routine Screen control flags
                                                                                                                                                                                                                                                                                Scrolling region active
1 = ON
DEVDEPND2 as returned by
                                                                                 SCR$L_DEVDEPND2 = 68. 0. 32. 0%.
                                                                                                                                                                                                                                                                                 GETDVI
                                                                                                                                                                  = 72, 0, 32, 0%,
                                                                                 SCR$L_EFN
                                                                                                                                                                                                                                                                                 Event flag number to use for
                                                                                                                                                                                                                                                                                 Q10s
                                                                                 SCR$L_BUFSIZ
SCR$L_FTDATA
SCR$L_FAB
SCR$L_RAB
                                                                                                                                                                = 76. 0. 32. 0%.
= 80. 0. 32. 0%.
= 112. 0. 32. 0%.
= 116. 0. 32. 0%:
                                                                                                                                                                                                                                                                                 Size of buffer
                                                                                                                                                                                                                                                                                Data area for use by SCRFT (32 bytes) FAB alloc for output file RAB alloc for output fil
                                                                                                                                                                                                                                                                                *** next free area is loc 120 ***
0090
0091
                                                          SCRSC_SIZE = 120;
                                                                                                                                                                                                                                                                      ! Size of block per terminal
```

SCH

Version:

'V04-000'

COPYRIGHT (c) 1978, 1980, 1982, 1984 BY DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS. ALL RIGHTS RESERVED.

THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY TRANSFERRED.

THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT CORPORATION.

DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.

FACILITY: Screen Management

ABSTRACT:

This file contains terminal type definitions and escape sequences which are needed by various routines in the screen package.

MODIFIED BY:

1-001 - Original. PLL 18-Oct-1982

Special characters

LITERAL = XX'08'. = XX'06'. = XX'0A'. BLANK BS

ESC

LB

blank (space) Backspace Form feed Line feed

= XX.0D. = XX'1B'. = XX 38 = XX

Carriage return Escape Left bracket (VT100)

Semi-colon

0140

0128 0129 0130

0138

0000

: F

SCR VO4

```
C 9
15-Sep-1984 23:25:09
15-Sep-1984 22:53:25
                                                                      VAX-11 Bliss-32 V4 0-742 Page $255$DUA28: [VMSLIB.SRC]SCRTERM.REQ; 1
! Null
! Length of internal buffer in FOREIGN ! Line/column bias in message
Non-graphics or unknown type
VT05 series terminal
VT5x series terminal
VT100 series terminal
Foreign terminal (FT1-8)
   Set cursor position
   Set cursor to home
   Cursor up
   Erase to end of line
   Erase to end of screen
   Set cursor position
Set cursor to home
   Down scroll
  Erase to end of screen 
Erase to end of line
   Set cursor position
Down scroll
```

901553456789010010101017778901234567 01553456789010010101017778901234567 01887

0192

0198

NULL

BUFSIZE

UNKNOWN

VTFOREIGN

VT05 VT52 VT100

VT05 Codes

VT05_SC VT05_HOME VT05_CUP VT05_EOL VT05_EOS

VT52 Codes

VT52 SC VT52 HOME VT52 DWN VT52 EOS VT52 EOL

VT100 Codes

VT100_SC VT100_DWN VT100_EOS VT100_EOL VT100_SGR VT100_SM

LITERAL

LITERAL

CB

= %x'00':

= 512 = XX'1F';

= 0. = 1. = 2. = 3. = 4:

= %X'0E'. = %X'1D'. = %X'1A'. = %X'1E'. = %X'1F';

= %x'59'. = %x'48'. = %x'49'. = %x'4A'. = %x'4B';

= %x'66'. = %x'40'. = %x'4A'. = %x'48'. = %x'60'. = %x'72';

Erase to end of screen Erase to end of line

! Select graphic rendition ! Set scrolling region

Miscellaneous constants

Terminal type definitions

SCR VO4

Page

5

SCR VO4

COMMAND QUALIFIERS

BLISS/LIB=LIB\$:SCRLIB/LIS=LIS\$:SCRLIB SRC\$:SCRTCB.REQ+SRC\$:SCRTERM.REQ

Run Time: 00:01.0 Elapsed Time: 00:01.8 Lines/CPU Min: 11825 Lexemes/CPU-Min: 32155 Memory Used: 15 pages Library Precompilation Complete

0437 AH-BT13A-SE

DIGITAL EQUIPMENT CORPORATION CONFIDENTIAL AND PROPRIETARY

